```
ANSWER 475 OF 575 CA COPYRIGHT 2004 ACS on STN
L5
     94:144428 CA
AN
     Entered STN: 12 May 1984
ED
     Plastering mortar composition
TI
     Tokuyama Soda Co., Ltd., Japan
PA
     Jpn. Kokai Tokkyo Koho, 5 pp.
     CODEN: JKXXAF
DT
     Patent
     Japanese
LA
     C04B013-00
IC
     58-3 (Cement and Concrete Products)
CC
FAN.CNT 1
                                             APPLICATION NO.
                                                               DATE
                       KIND DATE
     PATENT NO.
                                             -----
                                                               _____
                              -----
                                                                19790402
                                             JP 1979-38339
                              19801011
                        A2
PΙ
     JP 55130847
                              19831220
                        B4
     JP 58057386
                              19790402
PRAI JP 1979-38339
     The plastering mortar contains cement 100, fly
     ash 10-50, gypsum 2-24 (as SO3), water
     -granulated slag 100-300, sulfonate 0.4-4 parts, and cellulose ether in an amt. (C) of (E-1)/10 .ltoreq. C .ltoreq. (E+1)/10, where E is the
     sulfonate content. Thus, a mortar contg. cement 100,
     fly ash 40, gypsum 10, water
     -granulated slag 150, Na lignosulfonate [8061-51-6] 0.75, and
     methylcellulose [9004-67-5] 0.06 part was coated on a concrete plate at 5
     mm thickness and cured. The coating had no cracking or efflorescence even
     after 3 mo.
ST
     plastering mortar
IT
     Mortar
       Plaster
         (from cement and slag, contg. sodium lignosulfonate and Me
```

cellulose)

```
ANSWER 475 OF 575 CA COPYRIGHT 2004 ACS on STN
L5
    94:144428 CA
AN
    Entered STN: 12 May 1984
BD
    Plastering mortar composition
TI
     Tokuyama Soda Co., Ltd., Japan
PA
     Jpn. Kokai Tokkyo Koho, 5 pp.
     CODEN: JKXXAF
     Patent
DT
     Japanese
LA
     C04B013-00
IÇ
    58-3 (Cement and Concrete Products)
CC
FAN.CNT 1
                                           APPLICATION NO.
                      KIND
     PATENT NO.
     ------
                                                            19790402
                                           JP 1979-38339
                            19801011
                      A2
     JP 55130847
PΙ
                      B4
                            19831220
     JP 58057386
PRAI JP 1979-38339
                            19790402
AB The plastering mortar contains cement 100, fly
     ash 10-50, gypsum 2-24 (as SO3), water
     -granulated slag 100-300, sulfonate 0.4-4 parts, and cellulose ether in an
     amt. (C) of (E-1)/10 .ltoreq. C .ltoreq. (E + 1)/10, where E is the
     sulfonate content. Thus, a mortar contg. cement 100,
     fly ash 40, gypsum 10, water
     -granulated slag 150, Na lignosulfonate [8061-51-6] 0.75, and
     methylcellulose [9004-67-5] 0.06 part was coated on a concrete plate at 5
     mm thickness and cured. The coating had no cracking or efflorescence even
     after 3 mo.
     plastering mortar
    Mortar
IT
       Plaster.
        (from cement and slag, contg. sodium lignosulfonate and Me
        cellulose)
```

J